


TITAN SERIES



TITAN 2-90

2 x 840 mm seal



- Capacity pump 300 m³/h
- Machine cycle 30-50 sec.
- Dimensions (l x w x h) 1180 x 2420 x 1150 mm
- Weight 850 kg
- Voltage 400V-3-50Hz (Other voltages available)
- Power 7,0 - 9,0 kW
- Compressed air consumption 100 NI / min. 6 bar



FULL AUTOMATIC SYSTEM



ADVANCED CONTROL SYSTEM



HYGIENIC DESIGN



Pure Vacuum

TITAN SERIES

AUTOMATIC DOUBLE-CHAMBER BELT VACUUM-PACKAGING MACHINE WITH A WORLDWIDE REPUTATION

- Heavy-duty full stainless-steel automatic packaging machines with conveyor belts for industrial applications
- Smart design for easy cleaning and optimum hygiene at all times
- Extensive command parameters for specific packaging requirements
- Intelligent full-colour Control Interface
- User-friendly and low-maintenance, comes with complete service programme
- Well-designed solid construction and high-quality materials guarantee reliability in every environment
- High capacity with efficient cost-saving operational process

FOOD PRODUCTS

Industrial Production - Wholesale - Export Packaging (meat, poultry, fish, cheese, vegetables, etc.)

- No contamination or bacterial multiplication, hence an extended shelf life resulting in:
 - cost savings (larger purchase orders, efficient cooking time spreading and minimising products losses)
 - increased turnover (more variation and spread in product range)
- Optimum product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of flavour)
- Professional product presentation
- Optimum packaging contributes to food safety and HACCP standards

NON-FOOD PRODUCTS

Electronics - Metal - Textiles - etc.

- Moisture-free packaging
- Air and dust-free packaging
- Volume-reducing packaging
- Scrape and scratch-free solution
- Tamper-proof packaging
- Sterile and contamination-free packaging

SPECIFICATIONS

GENERAL

- Double chamber model with automatic lid and conveyor belts
- Robust Full Stainless Construction
- Conveyor belts with quick-release attachment for easy cleaning
- Full colour wide screen
- Intuitive Graphic Interface
- 20 programs adjustable in % and mbar / hPa
- 6 languages operational mode
- Program access security
- Sealing mechanism mounted in lid
- Adjustable belt height

PACKAGING FUNCTIONS

- **Vacuum**
Optimal final vacuum 99,9% (0,1 Mbar)
- **Soft-air**
Controlled ventilation for protection of product and packaging

SEALING SYSTEMS

- **Double-soudure**
2 x 3,5 mm convex sealing wire for optimal moisture elimination (double protection)
- **Cut-off seal**
1 x 3,5 mm convex sealing wire + 1 x 1,1 mm round cutting wire / One time setting (cut off remaining flap)
- **1-2 Cut-off seal**
1 x 3,5 mm convex sealing wire + 1 x 1,1 mm round cutting wire / Independent time setting (shrink bags)
- **Wide Seal**
1 x 8,0 mm flat sealing wire

OPERATIONAL CONTROL FUNCTIONS

- **Advanced Sensor Control**
Set percentage pressure for vacuum for accurate and constant packaging results / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum / PC interface
- **Liquid Sensor Control**
Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection. 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum / PC interface

SUPPORT CONTROL FUNCTIONS

- STOP button for partial/full cycle interrupt
- Digital maintenance program for pump / Operating hours counter / Service indicator programs / Sleeper function etc.

OPTIONAL FUNCTIONS / ACCESSORIES

- External transport conveyor
- Lid filler plates for lid for faster process
- Service kit for standard maintenance
- Preparation for external pump

Optional

Standard

Sentence and printing errors reserved

